

# Harley-Davidson Pan America 1250 1252 maintenance sheet

Pan America 1250 · 152 PS (112 kW)

Years : 2021-present      Generated on : 12 October 2026

## Technical specifications

Petrol

Engine code : Harley Revolution Max 1250

1 252 cm³

Manual 6

## Maintenance schedule

≈: estimated reference — the vehicle’s service indicator prevails.

| ITEM                            | INTERVAL             |                                                                                                                                                                                   |
|---------------------------------|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Oil and filter change           | ≈ 8,000 km or 1 year | JASO MA or MA2 approved four-stroke motorcycle oil (JASO MB on scooters): an “energy conserving” car oil makes the wet clutch slip. Change it more often in city use or on track. |
| Brake fluid                     | Every 2 years        | Replace the fluid in both circuits (and the hydraulic clutch if fitted), whatever the mileage; dark fluid has absorbed moisture.                                                  |
| Fork oil                        | ≈ 30,000 km          | Fork oil change and seal check; an oil film on the tubes means a seal needs replacing before it contaminates the brake caliper.                                                   |
| Chain kit (chain and sprockets) | ≈ 25,000 km          | Lubricate and check the tension every 500 to 1,000 km and after rain; replace chain and sprockets together when the chain no longer holds its tension or the teeth are hooked.    |
| Spark plugs                     | Every 48,000 km      | Replace the full set; worn plugs raise consumption and cause misfires.                                                                                                            |
| Air filter                      | Every 16,000 km      | Replace more often in dusty conditions.                                                                                                                                           |
| Coolant                         | Every 3 years        | Replace the coolant and check the hoses and radiator; check the level cold between services.                                                                                      |

## Service record

| DATE | MILEAGE | WORK DONE | WORKSHOP |
|------|---------|-----------|----------|
|      |         |           |          |
|      |         |           |          |
|      |         |           |          |

| DATE | MILEAGE | WORK DONE | WORKSHOP |
|------|---------|-----------|----------|
|      |         |           |          |
|      |         |           |          |
|      |         |           |          |
|      |         |           |          |
|      |         |           |          |
|      |         |           |          |
|      |         |           |          |
|      |         |           |          |

Indicative intervals and costs: adapt maintenance to the engine, use and manufacturer's instructions.

Full schedule and updates : <https://auto-karnet.com/en/maintenance/harley-davidson/pan-america/pan-america-2021/1252-152>