AutoKarnet

Toyota ProAce 1.6 HDi 90 maintenance sheet

ProAce I · 90 PS (66 kW)

Years : 2013–2016 Generated on : 04 November 2026

Technical specifications

Diesel | Engine code : DV6 1.6 HDi | 1 560 cm³ | Manual 5

Maintenance schedule

≈: estimated reference — the vehicle's service indicator prevails.

ITEM	INTERVAL	
Oil and filter change	**≈ 15,000 km or 1 year**	Typical interval: 15,000 km or 12 months, whichever comes first. ACEA C2 / C3 — Engine, model year and severe use may require a shorter interval; do not exceed the service warning. The listed oil approvals are not interchangeable: check the one for the engine.
Brake fluid	**Every 2 years**	Brake fluid: generally replaced every 2 years; inspect the brakes at each service.
Timing belt	**175,000 km or 10 years**	Replace the complete kit (belt, tensioners and usually the water pump) at whichever comes first; a broken belt destroys the engine.
Air filter	**60,000 km or 4 years**	Replace more often in dusty conditions.
Cabin filter	**30,000 km or 2 years**	Often replaced at each service; earlier if smells or persistent misting appear.
Diesel filter	**60,000 km or 4 years**	Drain any water at each service; a clogged filter causes loss of power.

Service record

DATE	MILEAGE	WORK DONE	WORKSHOP

DATE	MILEAGE	WORK DONE	WORKSHOP

> Indicative intervals and costs: adapt maintenance to the engine, use and manufacturer’s instructions.

Full schedule and updates : https://auto-karnet.com/en/maintenance/toyota/proace/proace-2-2013-2016/1-6-hdi-90-90